

[illegible]

```
EEEEEEEEEE RRRRRRRR RRRRRRRR SSSSSSSS UU UU BBBB BBBB 77777777 333333 000000
EEEEEEEEEE RRRRRRRR RRRRRRRR SSSSSSSS UU UU BBBB BBBB 77777777 333333 000000
EE          RR      RR RR      RR SS      SS      UU      UU BB      BB 77      77 33      33 00      00
EE          RR      RR RR      RR SS      SS      UU      UU BB      BB 77      77 33      33 00      00
EE          RR      RR RR      RR SS      SS      UU      UU BB      BB 77      77 33      33 00      00
EE          RR      RR RR      RR SS      SS      UU      UU BB      BB 77      77 33      33 00      00
EEEEEEEEEE RRRRRRRR RRRRRRRR SSSSSS  SS      UU      UU BBBB BBBB 77      77 33      33 00      00
EEEEEEEEEE RRRRRRRR RRRRRRRR SSSSSS  SS      UU      UU BBBB BBBB 77      77 33      33 00      00
EE          RR      RR RR      RR SS      SS      UU      UU BB      BB 77      77 33      33 00      00
EE          RR      RR RR      RR SS      SS      UU      UU BB      BB 77      77 33      33 00      00
EE          RR      RR RR      RR SS      SS      UU      UU BB      BB 77      77 33      33 00      00
EEEEEEEEEE RRR      RR RR      RR SSSSSSSS UU      UU BBBB BBBB 77      77 333333 000000
EEEEEEEEEE RRR      RR RR      RR SSSSSSSS UU      UU BBBB BBBB 77      77 333333 000000

LL          IIIIII SSSSSSSS
LL          IIIIII SSSSSSSS
LL          II      SS
LL          II      SS
LL          II      SS
LL          II      SS
LL          II      SSSSSS
LL          II      SSSSSS
LL          II      SS
LL          II      SS
LL          II      SS
LL          II      SS
LLLLLLLLLL IIIIII SSSSSSSS
LLLLLLLLLL IIIIII SSSSSSSS
```


(4)	257	EX\$INIBOOTADP - INITIALIZE THE BOOT DEVICE ADAPTER
(5)	391	EX\$SHUTDWNADP - SHUTDOWN ANY ADAPTERS DURING BUGCHECK
(5)	392	EX\$STARTUPADP - STARTUP ANY ADAPTERS
(6)	461	EX\$DUMPCPUREG - DUMP CPU-SPECIFIC IPR'S
(7)	577	EX\$READ TODR (P) - READ TIME-OF-DAY CLOCK
(8)	666	EX\$WRITE TODR (P) - WRITES TIME-OF-DAY CLOCK
(9)	724	EX\$REGSAVE - SAVE CPU-SPECIFIC IPR'S
(10)	786	EX\$REGRESTOR - RESTORE CPU-SPECIFIC IPR'S
(11)	846	EX\$INIPROCREG - CPU-DEPENDENT INITIALIZATION OF IPR'S
(13)	985	SYSL\$CLRSBIA
(14)	1025	EX\$TEST_CSR
(15)	1197	ADPLINK = LINK ADAPTER CONTROL BLOCK INTO ADP LIST


```
0000 1      .NOSHOW CONDITIONALS
0000 5
0000 9
0000 11     .TITLE  ERRSUB730 - ERROR SUBROUTINES FOR VAX 11/730
0000 13
0000 17
0000 21
0000 22     .IDENT  'V04-002'
0000 23
0000 24 :
0000 25 :*****
0000 26 :*
0000 27 :*  COPYRIGHT (c) 1978, 1980, 1982, 1984 BY
0000 28 :*  DIGITAL EQUIPMENT CORPORATION, MAYNARD, MASSACHUSETTS.
0000 29 :*  ALL RIGHTS RESERVED.
0000 30 :*
0000 31 :*  THIS SOFTWARE IS FURNISHED UNDER A LICENSE AND MAY BE USED AND COPIED
0000 32 :*  ONLY IN ACCORDANCE WITH THE TERMS OF SUCH LICENSE AND WITH THE
0000 33 :*  INCLUSION OF THE ABOVE COPYRIGHT NOTICE. THIS SOFTWARE OR ANY OTHER
0000 34 :*  COPIES THEREOF MAY NOT BE PROVIDED OR OTHERWISE MADE AVAILABLE TO ANY
0000 35 :*  OTHER PERSON. NO TITLE TO AND OWNERSHIP OF THE SOFTWARE IS HEREBY
0000 36 :*  TRANSFERRED.
0000 37 :*
0000 38 :*  THE INFORMATION IN THIS SOFTWARE IS SUBJECT TO CHANGE WITHOUT NOTICE
0000 39 :*  AND SHOULD NOT BE CONSTRUED AS A COMMITMENT BY DIGITAL EQUIPMENT
0000 40 :*  CORPORATION.
0000 41 :*
0000 42 :*  DIGITAL ASSUMES NO RESPONSIBILITY FOR THE USE OR RELIABILITY OF ITS
0000 43 :*  SOFTWARE ON EQUIPMENT WHICH IS NOT SUPPLIED BY DIGITAL.
0000 44 :*
0000 45 :*
0000 46 :*****
0000 47 :
0000 48 :++
0000 49 :
0000 50 : FACILITY:
0000 51 :
0000 52 :     EXECUTIVE, LOADABLE SUBROUTINES USED BY POWERFAIL AND BUGCHECK.
0000 53 :
0000 54 : ABSTRACT:
0000 55 :
0000 56 : LOADABLE SUBROUTINES USED BY POWERFAIL AND BUGCHECK.
0000 57 :
0000 58 : AUTHOR:
0000 59 :
0000 60 :     N. KRONENBERG, JULY 2, 1979.
0000 61 :
0000 62 : MODIFIED BY:
0000 63 :
0000 64 :     V04-003 WMC00001      Wayne Cardoza      13-Sep-1984
0000 65 :     CRD reporting must not be turned off for VENUS.
0000 66 :
0000 67 :     V04-002 CWH4002      CW Hobbs      08-Sep-1984
0000 68 :     Correct typo in TCM0010, use '-' instead of '='.
0000 69 :
0000 70 :     V04-001 TCM0010      Trudy C. Matthews  07-Sep-1984
0000 71 :     For the venus processor: move turning on cache from routine
```



```
0000 72 : EXE$INIPROCREG to a new routine: INIS$CACHE. Correct the
0000 73 : order in which registers are saved on the stack in EXE$REGSAVE.
0000 74 :
0000 75 : V03-022 TCM0009 Trudy C. Matthews 30-Jul-1984
0000 76 : When turning off CRD interrupts in EXE$INIPROCREG for VENUS,
0000 77 : read the processor register and write it back to preserve
0000 78 : the state of other bits in the register.
0000 79 :
0000 80 : V03-021 TCM0008 Trudy C. Matthews 23-Jul-1984
0000 81 : Remove venus code that queries the console for how to set up
0000 82 : cache and FBOX state. Instead always turn the cache and
0000 83 : FBOX on (and let the normal error handling code turn it off
0000 84 : if its bad).
0000 85 :
0000 86 : V03-020 DWT0214 David W. Thiel 02-May-1984
0000 87 : Revise MicroVAX I TODR register simulation.
0000 88 :
0000 89 : V03-019 KDM0096 Kathleen D. Morse 27-Mar-1984
0000 90 : Add missing indirection in MicroVAX I memory CSR
0000 91 : CRD enabling.
0000 92 :
0000 93 : V03-018 KPL0101 Peter Lieberwirth 4-Mar-1984
0000 94 : Add extra vectors now defined in SYSLOAVEC. These vectors
0000 95 : are insurance for v4.x
0000 96 :
0000 97 : V03-017 KPL0100 Peter Lieberwirth 12-Feb-1984
0000 98 : Change RPB$B_BOOTNDT to RPB$W_BOOTNDT, since BI devices
0000 99 : will have 16-bit device types.
0000 100 :
0000 101 : V03-016 KDM0092 Kathleen D. Morse 23-Jan-1984
0000 102 : Correct the number of cpu-specific IPRs logged for the
0000 103 : 11/730 and MicroVAX I cpus.
0000 104 :
0000 105 : V03-015 CWH8001 CW Hobbs 5-Dec-1983
0000 106 : Add entry points for EXE$READP_TODR and EXE$WRITEP_TODR
0000 107 : to access physical TODR register for Nautilus CPU. For
0000 108 : other processors, these amount to duplicate labels on
0000 109 : EXE$READ_TODR and EXE$WRITE_TODR.
0000 110 :
0000 111 : V03-014 KTA3088 Kerbey T. Altmann 17-Oct-1983
0000 112 : Fix bug in 730 conditional for EXE$INIBOOTADP.
0000 113 :
0000 114 : V03-013 KDM0081 Kathleen D. Morse 13-Sep-1983
0000 115 : Create Micro-VAX I version.
0000 116 :
0000 117 : V03-012 KDM0055 Kathleen D. Morse 12-Jul-1983
0000 118 : Move IPR PME into the cpu-dependent register save and
0000 119 : restore routines.
0000 120 :
0000 121 : V03-011 KDM0049 Kathleen D. Morse 07-Jul-1983
0000 122 : Add the following processor registers to the cpu-specific
0000 123 : dump IPRs routine: ICR, TODR, ACCS. Add usage of
0000 124 : register: EXE$READ_TODR and EXE$WRITE_TODR.
0000 125 :
0000 126 : V03-010 KDM0048 Kathleen D. Morse 07-Jul-1983
0000 127 : Add loadable routines for referencing the time-of-day
0000 128 : clock: EXE$READ_TODR, EXE$WRITE_TODR.
```


0000	129	:	
0000	130	:	
0000	131	:	V03-009 TCM0007 Trudy C. Matthews 02-Jun-1983
0000	132	:	Fix routine SYSLSCLRSBIA so that it calculates the address
0000	133	:	of SBI adapter register space correctly.
0000	134	:	
0000	135	:	V03-008 TCM0006 Trudy C. Matthews 9-Feb-1983
0000	136	:	Store enable/disable state of 11/790 cache and FBOX in
0000	137	:	EXESGB_CPUDATA cell during system initialization.
0000	138	:	
0000	139	:	V03-007 TCM0005 Trudy C. Matthews 11-Jan-1983
0000	140	:	Add routine SYSLSCLRSBIA. Add SBIA register initialization
0000	141	:	to EXESINIPROCREG. Add 11/790 machine check handler to
0000	142	:	EXESTEST CSR. Change 11/780 machine check handler to
0000	143	:	write PRS_SBIFS back to itself to clear error bits.
0000	144	:	Add labels for two "extra" routines, that can be patched
0000	145	:	if extra vectors from SYS to SYSLOA are needed in between
0000	146	:	major releases. Make EXESDUMPCPUREG log the SBI registers
0000	147	:	from the SBI the 11/790 system disk is on.
0000	148	:	
0000	149	:	V03-006 TCM0004 Trudy C. Matthews 3-Jan-1983
0000	150	:	Add more 11/790-specific code.
0000	151	:	
0000	152	:	V03-005 TCM0003 Trudy C. Matthews 17-Dec-1982
0000	153	:	Add conditional assembly switch to the invocations
0000	154	:	of 11/790-specific definition macros.
0000	155	:	
0000	156	:	V03-004 TCM0002 Trudy C. Matthews 15-Dec-1982
0000	157	:	Added 11/790-specific code to EXESINIPROCREG.
0000	158	:	
0000	159	:	V03-003 TCM0001 Trudy C. Matthews 13-Dec-1982
0000	160	:	Added 11/790-specific code to power down/power up
0000	161	:	routines.
0000	162	:	
0000	163	:	V03-002 KTA3018 Kerbey T. Altmann 30-Oct-1982
0000	164	:	Remove CI and UBA routines to another module.
0000	165	:	--


```
0000 167
0000 168 :
0000 169 : MACRO LIBRARY CALLS:
0000 170 :
0000 171
0000 172 $ADPDEF ;DEFINE ADAPTER OFFSETS
0000 173 $BQODEF ;DEFINE BOOT QIO OFFSETS
0000 174 $BTDDDEF ;DEFINE BOOT DEVICE TYPES
0000 175 $EMBCRDEF ;DEFINE ERROR MSG BUFFER OFFSETS
0000 176 $IDBDEF ;DEFINE INTERRUPT DISPATCH OFFSETS
0000 177 $IPLDEF ;DEFINE INTERRUPT PRIORITY LEVELS
0000 178 $MBADEF ;DEFINE MASSBUS ADAPTER OFFSETS
0000 179 $NDTDEF ;DEFINE NEXUS DEVICE TYPES
0000 180 $PRDEF ;DEFINE INTERNAL PROCESSOR REGISTERS
0000 181 $RPBDEF ;DEFINE RESTART PARAM BLOCK OFFSETS
0000 182 $SSDEF ;DEFINE SYSTEM STATUS CODES
0000 183 $UBADEF ;DEFINE UNIBUS ADAPTER OFFSETS
0000 195
0000 199
0000 203
0000 205 $PR730DEF ;DEFINE 11/730 INTERNAL PROCESSOR REGS
0000 207
0000 211 :
0000 212 : EQUATED SYMBOLS:
0000 213 :
0000 218
0000 223
00000000 0000 225 C780_LIKE = 0
00000001 0000 226 C750_LIKE = 1
0000 228
0000 233
0000 238
0000 239 :
0000 240 : Define labels for two "extra" routines. This reserves some vectors from
0000 241 : SYS.EXE into SYSLOAxxx.EXE that can be patched if another routine must
0000 242 : be added in between major releases.
0000 243 :
0000 244 EXE$EXTRA1:: ; aligned
0000 245 EXE$EXTRA2:: ; aligned
0000 246 EXE$EXTRA3:: ; aligned
0000 247 EXE$EXTRA4:: ; aligned
0000 248 EXE$EXTRA5:: ; aligned
0000 249 EXE$EXTRA6:: ; packed
0000 250 EXE$EXTRA7:: ; packed
0000 251 EXE$EXTRA8:: ; packed
0000 252 EXE$EXTRA9:: ; packed
0000 253 EXE$EXTRA10:: ; packed (think this is enough?)
0000 254
00 0000 255 HALT ; Error if these labels are used.
```



```
0001 257 .SBTTL EXESINIBOOTADP - INITIALIZE THE BOOT DEVICE ADAPTER
0001 258
0001 259 :+ EXESINIBOOTADP - GET THE SYSTEM BOOT DEVICE ADAPTER AND INIT IT.
0001 260 : THIS ROUTINE IS CALLED FROM BUGCHECK BEFORE THE BOOTDRIVER IS CALLED.
0001 261
0001 262 : INPUTS:
0001 263
0001 264 : R6 = RPB ADDRESS
0001 265
0001 266 : OUTPUTS:
0001 267
0001 268 : R0-R2 DESTROYED
0001 269 : OTHER REGISTERS PRESERVED
0001 270 :-
0001 271
0000 272 .PSECT SYSLOA, LONG
0000 273 .ENABLE LSB
0000 274
0000 275 EXESINIBOOTADP:: ;SUBROUTINE ENTRY
0000 276
0000 277
66 A6 91 0000 278 CMPB RPB$B_DEVTYPE(R6),- ;IS BOOT DEVICE THE CONSOLE
40 8F 0003 279 #BTD$R_CONSOLE ;BLOCK STORAGE DEVICE?
2B 13 0005 280 BEQL 40$ ;YES, RETURN
50 60 A6 D0 0007 281 MOVL RPB$L_ADPVIR(R6),R0 ;GET ADDR OF ADAPTER REG SPACE
000B 282
000B 327
000B 331
000B 332 INI_UBADP: ;INIT UBA
000B 333
000B 341
000B 343
000B 347
37 00 DA 000B 349 MTPR #0,#PR730$_UBRESET ;INIT UBI AND UNIBUS
000E 351
000E 356
000E 358
000E 360 :
000E 361 : CHECK THE VMB VERSION NUMBER. IF IT EXISTS AND IF IT IS 7 OR GREATER, THEN
000E 362 : SEE IF ANY UNIBUS MAP REGISTERS TO DISABLE.
000E 363 :
000E 364
52 34 A6 D0 000E 365 MOVL RPB$L_IOVEC(R6),R2 ;PICK UP THE IOVECTOR FROM RPB
51 10 A2 B2 0012 366 MCOMW BQ0$W_VERSION(R2),R1 ;GET VMB VERSION NUMBER 1'S COMPLEMENTED
12 A2 51 B1 0016 367 CMPW R1,BQ0$W_VERSION+2(R2) ;CHECK AGAINST CHECK WORD IN VMB
16 12 001A 368 BNEQ 40$ ;IF NOT, ASSUME NO VERSION NUMBER
07 10 A2 B1 001C 369 CMPW BQ0$W_VERSION(R2),#7 ;VERSION 7 OR GREATER OF VMB?
10 1F 0020 370 BLSSU 40$ ;NO, DON'T BOTH WITH UMR'S
52 24 A2 D0 0022 371 MOVL BQ0$L_UMR_DIS(R2),R2 ;GRAB THE NUMBER OF UMR'S TO DISABLE
0A 13 0026 372 BEQL 40$ ;NONE, LEAVE
0028 373
0028 377
0028 378 :
0028 379 : THIS CODE IS EXECUTED FOR ALL PROCESSORS. ITS DISABLES ANY UNIBUS MAP
0028 380 : REGISTERS ASSOCIATED WITH UNIBUS MEMORY TO PREVENT CONTENTION BETWEEN
0028 381 : SBI AND UNIBUS ADDRESSES.
0028 382 :
0028 383
```


ERRSUB730
V04-002

- ERROR SUBROUTINES FOR VAX 11/730^{H 6}
EXESINIBOOTADP - INITIALIZE THE BOOT DEV 13-SEP-1984 15:49:22 [SYSLOA.SRC]ERRSUB.MAR;5
16-SEP-1984 00:54:20 VAX/VMS Macro V04-00

Page 6
(4)

51	0800	C0	DE	0028	384	MOVAL	UBASL_MAP(R0),R1	:ADDRESS OF FIRST REGISTER
		81	D4	002D	385	CLRL	(R1)+	:DISABLE IT
	FB	52	F5	002F	386	SOBGR	R2,30\$:LOOP UNTIL ALL DONE
			05	0032	388	RSB		:DONE WITH UBA INIT
				0033	389	.DISABLE	LSB	

```
0033 391      .SBTTL  EX$SHUTDWNADP - SHUTDOWN ANY ADAPTERS DURING BUGCHECK
0033 392      .SBTTL  EX$STARTUPADP - STARTUP ANY ADAPTERS
0033 393      :+
0033 394      : EX$SHUTDWNADP - SHUTDOWN ANY ADAPTERS DURING BUGCHECK
0033 395      : THIS ROUTINE IS CALLED FROM BUGCHECK BEFORE THE DUMP IS TAKEN TO
0033 396      : ENSURE THAT ALL ADAPTERS THAT NEED TO BE QUIESENT ARE.
0033 397      :
0033 398      : INPUTS:
0033 399      :
0033 400      :     IPL = 31
0033 401      :
0033 402      : OUTPUTS:
0033 403      :
0033 404      :     OTHER REGISTERS PRESERVED
0033 405      :-
0033 406      :     .ENABLE LSB
0033 407
0033 408  EX$STARTUPADP::
0033 409      PUSH  #^M<R0,R1,R2,R4>      ; Save a register
51  7A'AF  DE 0035 410      MOVAL  B^ADP_TBL_UP,R1      ; Address of startup table
0033 411      BRB    5$                  ; Join common code
0033 412
0033 413  EX$SHUTDWNADP::
0033 414      PUSH  #^M<R0,R1,R2,R4>      ; Save a register
51  62'AF  DE 003D 415      MOVAL  B^ADP_TBL_DWN,R1      ; Address of shutdown table
FFFFF7FC'9F DE 0041 416  5$: MOVAL  @#<IOCSGL_ADPLIST- -
0033 417      ADP$L [LINK],R2          ; Get pointer to head of adapter list
52  04 A2  DO 0048 418  10$: MOVL   ADP$L_LINK(R2),R2      ; Flink onward
0033 419      BEQL   20$                ; Branch if at end of list
54  62  DO 004E 420      MOVL   ADP$L_CSR(R2),R4          ; Get address of CSR
50  0E A2  DO 0051 421      MOVZWL ADP$W_ADPTYPE(R2),R0      ; Get adapter type code
50  6140  DE 0055 422      MOVAL  (R1)[R0],R0          ; Get table entry of adap shutdown
00  B040  16 0059 423      JSB    @<R0>[R0]          ; Call adapter shutdown
0033 424      BRB    10$                ; Next adapter
0033 425
0033 426  20$: POPR   #^M<R0,R1,R2,R4>
0033 427  30$: RSB
0033 428
0033 429      :
0033 430      : Table of addresses of adapter shutdown routines ordered
0033 431      : by adapter type in ADP$W_ADPTYPE.
0033 432      :
0033 433
0033 434  ADP_TBL_DWN:
0033 435      .LONG  30$-                ; Address table start
FFFFF7FF 0062 436      .LONG  30$-                ; 0-MBA
FFFFF7FB 0066 437      .LONG  30$-                ; 1-UBA
FFFFF7F7 006A 438      .LONG  30$-                ; 2-DR32
FFFFF7F3 006E 439      .LONG  30$-                ; 3-MA780
FFFFF7E7 0072 440      .LONG  C1$SHUTDOWN-        ; 4-CI
FFFFF7E3 0076 441      .LONG  30$-                ; Rsvrd for future expansion
0033 442
0033 443      :
0033 444      : Table of addresses of adapter startup routines ordered
0033 445      : by adapter type in ADP$W_ADPTYPE.
0033 446      :
0033 447
0033 448
0033 449
0033 450
0033 451  ADP_TBL_UP:
0033      : Address table start
```


ERRSUB730
V04-002

J 6
- ERROR SUBROUTINES FOR VAX 11/730
EXESSTARTUPADP - STARTUP ANY ADAPTERS

16-SEP-1984 00:54:20 VAX/VMS Macro V04-00
13-SEP-1984 15:49:22 [SYSLOA.SRC]ERRSUB.MAR;5

Page 8
(5)

FFFFFF86'	007A	452	.LONG	MBASINITIAL-.	:	0-MBA
FFFFFF82'	007E	453	.LONG	UBASINITIAL-.	:	1-UBA
FFFFFFDF	0082	454	.LONG	30\$-.	:	2-DR32
FFFFFF7A'	0086	455	.LONG	MASINITIAL-.	:	3-MA780
FFFFFFD7	008A	456	.LONG	30\$-.	:	4-CI
FFFFFFD3	008E	457	.LONG	30\$-.	:	Rsvrd for future expansion
	0092	458				
	0092	459	.DISABLE	LSB		

```
0092 461 .SBTTL EXESDUMPCPUREG - DUMP CPU-SPECIFIC IPR'S
0092 462 :+
0092 463 : DUMP CPU-SPECIFIC IPR'S INTO ERROR MESSAGE BUFFER.
0092 464 :
0092 465 : TWENTY-FOUR LONGWORDS ARE RESERVED IN THE EMB FOR CPU-SPECIFIC
0092 466 : IPR'S. THE FORMATS FOR VARIOUS CPU'S ARE:
0092 467 :
0092 468 : 11/780:      11/750:      11/730:      11/790:      uVAX I:
0092 469 :
0092 470 : ICR          ICR          ICR          ICR          UNUSED(0)
0092 471 : TODR         TODR         TODR         TODR         APPROX TODR
0092 472 : ACCS          ACCS          ACCS          ACCS          UNUSED(0)
0092 473 : SBIFS        TBDR          21 UNUSED(0)  SBISTS (1st SBI)  21 UNUSED(0)
0092 474 : SBISC        CADR
0092 475 : SBIMT        MCSR
0092 476 : SBIER        CAER
0092 477 : SBIS        CMIRR
0092 478 : 16 SBI SILO  16 UNUSED(0)      16 SBI SILO
0092 479 :
0092 480 : INPUTS:
0092 481 :
0092 482 :      R0 - ADDR IN EMB OF START OF CPU-SPECIFIC REGISTERS=
0092 483 :      OFFSET EMB$L_CR_CPUREG
0092 484 :
0092 485 : OUTPUTS:
0092 486 :
0092 487 :      R0,R1 DESTROYED
0092 488 :      ALL OTHER REGISTERS PRESERVED
0092 489 : -
0092 490 :
0092 491 : .ENABL LSB
0092 492 :
0092 493 EXESDUMPCPUREG:: ;SUBROUTINE ENTRY
0092 494
0092 495
0092 509
0092 510
0092 524
0092 525
0092 527 MFPR #PR730$_ICR,(R0)+ ;LOG INTERVAL COUNT REG,
0092 528 MFPR #PR730$_TODR,(R0)+ ; TIME-OF-DAY REG,
0092 529 MFPR #PR730$_ACCS,(R0)+ ; ACCELERATOR CONTROL REG.
0092 530 MOVL #<<EMB$L_CR_CODE - EMB$L_CR_CPUREG>/4>-3, R1 ; -3 FOR ICR,
0092 531 ; TODR, AND ACCS ALREADY LOGGED.
0092 532 ; THERE ARE NO OTHER CPU-SPECIFIC
0092 533 10$: CLRL (R0)+ ; REGISTERS TO LOG, SO ZERO THE
0092 534 SOBGTR R1, 10$ ; SPACE IN THE ERROR MSG BUFFER
0092 535
0092 536
0092 537
0092 538
0092 539
0092 540
0092 541
0092 542
0092 543
0092 544
0092 545
0092 546
0092 547
0092 548
0092 549
0092 550
0092 551
0092 552
0092 553
0092 554
0092 555
0092 556
0092 557
0092 558
0092 559
0092 560
0092 561
0092 562
0092 563
0092 564
0092 565
0092 566
0092 567
0092 568
0092 569
0092 570
0092 571
0092 572 90$:
0092 573 RSB
0092 574 .DISABLE LSB
0092 575
```

80 1A DB 0092 527 MFPR #PR730\$_ICR,(R0)+ ;LOG INTERVAL COUNT REG,
80 1B DB 0092 528 MFPR #PR730\$_TODR,(R0)+ ; TIME-OF-DAY REG,
80 28 DB 0092 529 MFPR #PR730\$_ACCS,(R0)+ ; ACCELERATOR CONTROL REG.
51 15 D0 0092 530 MOVL #<<EMB\$L_CR_CODE - EMB\$L_CR_CPUREG>/4>-3, R1 ; -3 FOR ICR,
; TODR, AND ACCS ALREADY LOGGED.
; THERE ARE NO OTHER CPU-SPECIFIC
; REGISTERS TO LOG, SO ZERO THE
; SPACE IN THE ERROR MSG BUFFER

80 D4 0092 533 10\$: CLRL (R0)+
FB 51 F5 0092 534 SOBGTR R1, 10\$

05 0092 572 90\$: RSB
0092 573 .DISABLE LSB
0092 574
0092 575


```
00A4 577 .SBTTL EXESREAD_TODR (P) - READ TIME-OF-DAY CLOCK
00A4 578 ;+
00A4 579 ; READS THE TIME-OF-DAY CLOCK, SINCE IT MAY BE ACCESSED IN
00A4 580 ; DIFFERENT WAYS: AS AN INTERNAL PROCESSOR REGISTER, AS PART
00A4 581 ; OF THE CONSOLE, OR BY READING AN ADDRESS IN I/O SPACE. IT
00A4 582 ; MAY ALSO BE IN DIFFERENT FORMATS AND HAVE TO BE CONVERTED.
00A4 583 ;
00A4 584 INPUTS:
00A4 585 ;
00A4 586 ; NONE.
00A4 587 ;
00A4 588 OUTPUTS:
00A4 589 ;
00A4 590 ; R0 - TODR VALUE
00A4 591 ; ALL OTHER REGISTERS PRESERVED
00A4 592 ; -
00A4 593 ;
00A4 594 EXESREADP_TODR:: ; SUBROUTINE ENTRY
00A4 595 ;
00A4 596 ; NAUTILUS PROCESSOR NEEDS TO USE A SEPARATE ROUTINE TO ACCESS PHYSICAL TODR
00A4 597 ; REGISTER IN THE CONSOLE PROCESSOR FOR TWO REASONS. FIRST, THE PHYSICAL
00A4 598 ; TODR HAS ONE SECOND RESOLUTION INSTEAD OF 10 MSEC RESOLUTION. SECOND, A
00A4 599 ; REFERENCE TO THE PHYSICAL TODR IS A VERY SLOW, NON-INTERRUPTIBLE ACTION.
00A4 600 ; NON-PHYSICAL NAUTILUS TODR REFERENCES WILL USE THE EXESREAD_TODR ENTRY
00A4 601 ; WHICH WILL FABRICATE THE TIME FROM THE QUADWORD SYSTEM TIME.
00A4 602 ;
00A4 603 ; NOT NAUTILUS - FALL THROUGH TO READ_TODR
00A4 604 ;
00A4 605 EXESREAD_TODR:: ; SUBROUTINE ENTRY
00A4 606 ;
00A4 607 ;
00A4 611 ;
00A4 612 ;
00A4 616 ;
00A4 617 ;
50 1B DB 00A4 619 MFPR #PR730$_TODR,R0 ; TODR IS A PROCESSOR REGISTER.
00A7 621 ;
00A7 622 ;
00A7 626 ;
00A7 662 ;
05 00A7 663 RSB
00A8 664 ;
```

```
00A8 666      .SBTTL EXESWRITE_TODR (P) - WRITES TIME-OF-DAY CLOCK
00A8 667      :+
00A8 668      : WRITES THE TIME-OF-DAY CLOCK, SINCE IT MAY BE ACCESSED IN
00A8 669      : DIFFERENT WAYS: AS AN INTERNAL PROCESSOR REGISTER, AS PART
00A8 670      : OF THE CONSOLE, OR BY READING AN ADDRESS IN I/O SPACE. IT
00A8 671      : MAY ALSO BE IN DIFFERENT FORMATS AND HAVE TO BE CONVERTED.
00A8 672      :
00A8 673      : INPUTS:
00A8 674      :
00A8 675      :     RO - CONTAINS VALUE TO BE WRITTEN INTO TODR
00A8 676      :
00A8 677      : OUTPUTS:
00A8 678      :
00A8 679      :     NEW TIME VALUE WRITTEN INTO TODR.
00A8 680      :     ALL REGISTERS PRESERVED.
00A8 681      :-
00A8 682
00A8 683 EXESWRITEP_TODR::                                ; SUBROUTINE ENTRY
00A8 684
00A8 685      : NAUTILUS PROCESSOR NEEDS TO USE A SEPARATE ROUTINE TO ACCESS PHYSICAL TODR
00A8 686      : REGISTER IN THE CONSOLE PROCESSOR FOR TWO REASONS. FIRST, THE PHYSICAL
00A8 687      : TODR HAS ONE SECOND RESOLUTION INSTEAD OF 10 MSEC RESOLUTION. SECOND, A
00A8 688      : REFERENCE TO THE PHYSICAL TODR IS A VERY SLOW, NON-INTERRUPTIBLE ACTION.
00A8 689      : NON-PHYSICAL NAUTILUS TODR REFERENCES WILL USE THE EXESWRITE_TODR ENTRY
00A8 690      : WHICH WILL FABRICATE A NEW QUADWORD SYSTEM TIME.
00A8 691
00A8 692      : NOT NAUTILUS - FALL THROUGH TO WRITE_TODR
00A8 693
00A8 694 EXESWRITE_TODR::                                ; SUBROUTINE ENTRY
00A8 695
00A8 696
00A8 700
00A8 701
00A8 705
00A8 706
1B  50  DA 00A8 708      MTPR    RO,#PR730$_TODR      ; TODR IS A PROCESSOR REGISTER.
00AB 710
00AB 711
00AB 715
00AB 716
00AB 721
05  00AB 722      RSB
```



```
00AC 724 .SBTTL EXE$REGSAVE - SAVE CPU-SPECIFIC IPR'S
00AC 725 :+
00AC 726 : EXE$REGSAVE - CALLED BY POWERFAIL TO SAVE CPU-SPECIFIC IPR'S ON
00AC 727 : THE STACK
00AC 728 :
00AC 729 : INPUTS: NONE
00AC 730 :
00AC 731 : OUTPUTS:
00AC 732 :
00AC 733 : RO DESTROYED
00AC 734 : OTHER GENERAL REGISTERS PRESERVED
00AC 735 : IPR'S SAVED ON THE STACK AS FOLLOWS:
00AC 736 :
00AC 737 : 11/780: 11/750: 11/730: 11/790: uVAX I:
00AC 738 :
00AC 739 : 0(SP) PME PME PME ACCS (none)
00AC 740 : 4(SP) SBIMT TBDR CSWP
00AC 741 : 8(SP) CADR PME
00AC 742 :
00AC 743 : -
00AC 744 :
00AC 745 : .ENABL LSB
00AC 746 :
00AC 747 EXE$REGSAVE:: ;SUBROUTINE ENTRY
01 BA 00AC 749 POPR #^M<R0> ;CLEAR RETURN FROM STACK
00AE 750
00AE 751
00AE 756
00AE 757
00AE 763
00AE 764
7E 3D DB 00AE 766 MFPR #PR730$_PME,-(SP) ;SAVE PERFORMANCE MONITOR ENABLE
00B1 768
00B1 769
00B1 776
60 17 00B1 777 JMP (R0) ;DONE, RETURN
00B3 779
00B3 783
00B3 784 .DSABL LSB
```

```
00B3 786 .SBTTL EXE$REGRESTOR - RESTORE CPU-SPECIFIC IPR'S
00B3 787 :+
00B3 788 EXE$REGRESTOR - CALLED BY POWERFAIL RECOVERY TO RESTORE CPU-SPECIFIC
00B3 789 IPR'S FROM THE STACK.
00B3 790
00B3 791 INPUTS:
00B3 792
00B3 793 R6 - TOP OF STACK
00B3 794 STACK SET UP AS DEFINED IN OUTPUTS OF EXE$REGSAVE.
00B3 795
00B3 796 OUTPUTS:
00B3 797
00B3 798 R0 DESTROYED
00B3 799 OTHER GENERAL REGISTERS PRESERVED
00B3 800 CPU-SPECIFIC IPR'S RESTORED FROM STACK
00B3 801 R6 - ADDRESS OF 1ST CPU-INDEPENDENT SAVED IPR
00B3 802
00B3 803 :-
00B3 804
00B3 805 .ENABL LSB
00B3 806
00B3 807 EXE$REGRESTOR::
00B3 809 POPR #^M<R0> ;SUBROUTINE ENTRY
00B5 810 ;CLEAR RETURN FROM STACK
00B5 811
00B5 816
00B5 817
00B5 823
00B5 824
3D 86 DA 00B5 826 MTPR (R6)+, #PR730$_PME ;RESTORE PERFORMANCE MONITOR ENABLE
00B8 828
00B8 829
00B8 837
60 17 00B8 838 JMP (R0) ;DONE, RETURN
00BA 843
00BA 844 .DSABL LSB
```



```
00BA 846 .SBTTL EXE$INIPROCREG - CPU-DEPENDENT INITIALIZATION OF IPR'S
00BA 847 :+
00BA 848 : EXE$INIPROCREG - PERFORM INITIALIZATION OF INTERVAL TIMER AND
00BA 849 : CPU-DEPENDENT REGISTERS. CALLED FROM INIT AND POWERFAIL.
00BA 850 :
00BA 851 : INPUTS:
00BA 852 :
00BA 853 : NONE
00BA 854 :
00BA 855 : OUTPUTS:
00BA 856 :
00BA 857 : NONE
00BA 858 :-
00BA 859
00BA 860 EXE$INIPROCREG:: ; INIT PROCESSOR REGISTERS
00BA 861
00BA 875
00BA 876 BBC S^#EXE$V_CRDENABL,- ; BRANCH IF FLAG CLEAR
00BC 877 @#EXE$GL_FLAGS,20$ ; (IGNORE ERRORS)
00C2 878 MOVL @#MMG$GL_SBICONF,R0 ; GET ADDR OF MEMORY CONTROLLER
00C9 879 MOVL (R0),R0 ; CONFIG REGISTER (1ST SLOT)
00CC 880 BISL #<1@28>,4(R0) ; SET CRD REPORT BIT
00D4 881
00D4 925 20$: BBS S^#EXE$V_NOCLOCK,- ; BRANCH IF NOT USING CLOCK
00D6 926 @#EXE$GL_FLAGS,30$
00DC 927
00DC 931
00DC 935
00DC 939
00DC 941 MTPR #-<10*1000>,S^#PR730$_NICR ; LOAD NEXT INTERVAL REGISTER
00E3 943
00E3 944 MTPR #^X800000D1,S^#PR$_ICCS ; CLEAR ERROR AND START CLOCK
00EA 945 30$: RSB ; AND RETURN
00EB 946
00EB 962
```

12 00000000'9F E1 00BA 876 BBC S^#EXE\$V_CRDENABL,- ; BRANCH IF FLAG CLEAR
50 00000000'9F D0 00BC 877 @#EXE\$GL_FLAGS,20\$; (IGNORE ERRORS)
50 60 D0 00C2 878 MOVL @#MMG\$GL_SBICONF,R0 ; GET ADDR OF MEMORY CONTROLLER
04 A0 10000000 8F C8 00C9 879 MOVL (R0),R0 ; CONFIG REGISTER (1ST SLOT)
0E 00000000'9F E0 00CC 880 BISL #<1@28>,4(R0) ; SET CRD REPORT BIT
0E 00000000'9F E0 00D4 881
0E 00000000'9F E0 00D4 925 20\$: BBS S^#EXE\$V_NOCLOCK,- ; BRANCH IF NOT USING CLOCK
0E 00000000'9F E0 00D6 926 @#EXE\$GL_FLAGS,30\$
0E 00000000'9F E0 00DC 927
0E 00000000'9F E0 00DC 931
0E 00000000'9F E0 00DC 935
0E 00000000'9F E0 00DC 939
19 FFFFD8F0 8F DA 00DC 941 MTPR #-<10*1000>,S^#PR730\$_NICR ; LOAD NEXT INTERVAL REGISTER
18 800000D1 8F DA 00E3 943
05 00E3 944 MTPR #^X800000D1,S^#PR\$_ICCS ; CLEAR ERROR AND START CLOCK
05 00EA 945 30\$: RSB ; AND RETURN
05 00EB 946
05 00EB 962


```
00EB 985      .SBTTL  SYSL$CLRSBIA
00EB 986      :++
00EB 987      : SYSL$CLRSBIA - ON 11/790, CLEAR SBIA ERROR REGISTERS
00EB 988      : - ON 11/780, 11/750, 11/730, AND MICRO-VAX I, THIS IS A NOP
00EB 989      :
00EB 990      : THIS ROUTINE IS CALLED TO CLEAR OUT SBIA ERROR BITS AFTER A MACHINE CHECK
00EB 991      : OCCURS (WHEN MACHINE CHECK IS HANDLED LOCALLY).
00EB 992      :
00EB 993      : THIS ROUTINE SHOULD BE CALLED AT IPL 31.
00EB 994      :
00EB 995      : INPUTS:
00EB 996      :     ABUS_TYPE      - AN ARRAY TYPE CODES; IDENTIFIES EACH ADAPTER ON THE
00EB 997      :     ABUS_VA        - AN ARRAY OF ADAPTER SPACE VA'S FOR EACH ADAPTER
00EB 998      :     ON THE ABUS.
00EB 999      :
00EB 1000     :
00EB 1001     : OUTPUTS:
00EB 1002     :     SBI ERROR BITS ARE CLEARED FOR EACH SBIA ON THE ABUS.
00EB 1003     :     ALL REGISTERS PRESERVED.
00EB 1004     :++
00EB 1005     SYSL$CLRSBIA::
05 00EB 1023     RSB                                ; AND RETURN
```



```
00EC 1025 .SBTTL EXESTEST_CSR
00EC 1026 :+
00EC 1031 EXESTEST_CSR - TEST A UNIBUS CONTROLLER CSR FOR EXISTENCE
00EC 1033 :
00EC 1034 THIS TEST IS CPU-DEPENDENT. THE FOLLOWING CPU'S ARE SUPPORTED:
00EC 1035 :
00EC 1036 11/780 -TEST CSR AND CHECK RESULT IN THE UBA STATUS REGISTER.
00EC 1037 11/750 -NON-EXISTENT CSR IS REPORTED VIA MACHINE CHECK AS A
00EC 1038 NON-EXISTENT MEMORY REFERENCE. CONNECT A TEMPORARY
00EC 1039 MACHINE CHECK HANDLER, TEST THE CSR, AND RESTORE THE
00EC 1040 ORIGINAL MACHINE CHECK HANDLER.
00EC 1041 11/730 -ACTION IS THE SAME AS FOR THE 11/750.
00EC 1042 11/790 -ACTION IS THE SAME AS FOR THE 11/780.
00EC 1043 MICRO-VAX I -ACTION IS SAME AS FOR THE 11/750.
00EC 1044 :
00EC 1045 THIS SUBROUTINE SHOULD BE CALLED VIA BRANCH OR JUMP TO SUBROUTINE AT IPL 31.
00EC 1046 :
00EC 1047 INPUTS:
00EC 1048 :
00EC 1049 R0 = CSR ADDRESS
00EC 1050 R6 = ADAPTER CONFIGURATION REGISTER ADDRESS
00EC 1051 :
00EC 1052 OUTPUTS:
00EC 1053 :
00EC 1054 R0 LOW BIT SET/CLEAR FOR EXISTENT/NONEX CSR
00EC 1055 OTHER REGISTERS PRESERVED.
00EC 1056 :-
00EC 1057 :
00EC 1058 .ENABL LSB
00EC 1059 :
00EC 1060 EXESTEST_CSR:: ;SUBROUTINE ENTRY
00EC 1061 :
06 BB 00EC 1062 PUSHR #^M<R1,R2> ;SAVE REGISTERS
00EE 1063 :
00EE 1122 :
00000024 00EE 1123 MCK_BER = ^X24 ;OFFSET INTO 750 MACHINE CHECK FRAME
00EE 1124 : ; FOR BUS ERROR REGISTER
00000003 00EE 1125 NEX = 3 ; BIT POSITION FOR NON-EXISTENT MEMORY
00EE 1130 :
00EE 1132 :
00EE 1133 : Test for non-UNIBUS I/O space address first (IDC specific code)
00EE 1134 :
51 56 00000800 8F C1 00EE 1135 ADDL3 #512*4,R6,R1 ;GET LOWEST LEGAL ADDRESS
51 50 D1 00F6 1136 CMPL R0,R1 ;IS CSR GREATER ?
50 05 1A 00F9 1137 BGTRU 10$ ;IF YES, DO CHECK
50 01 9A 00FB 1138 MOVZBL #SS$_NORMAL,R0 ;NO CHECK TO DO, EXIT
38 11 00FE 1139 BRB TEST_DONE_2 ;
0100 1141 :
51 00000000 GF D0 0100 1142 10$: MOVL G^EXE$GL_SCB,R1 ;GET SCB ADDRESS
04 A1 DD 0107 1143 PUSHL 4(R1) ;SAVE CURRENT MCHECK HANDLER ADDR
52 5E D0 010A 1144 MOVL SP,R2 ;MARK CURRENT STACK POSITION
04 A1 1C AF DE 010D 1145 MOVAL B^MCHK_HANDLER,4(R1) ;CONNECT TEMP MCHECK HANDLER
60 B5 0112 1146 TSTW (R0) ;ATTEMPT TO READ CSR
50 01 9A 0114 1147 OK: MOVZBL #SS$_NORMAL,R0 ;IF NO MCHECK, SET STATUS TO
0117 1148 : ; SUCCESS
1B 11 0117 1149 BRB TEST_DONE ;JOIN COMMON EXIT
0119 1150
```

```
0119 1151 :  
0119 1152 : TEMPORARY CSR TEST MACHINE CHECK HANDLER  
0119 1153 :  
0119 1154 :  
0119 1155 .ALIGN LONG ;REQ'D MACHINE CHECK ALIGNMENT  
011C 1156 MCHK_HANDLER: ;  
011C 1157  
011C 1161  
26 0F DA 011C 1163 MTPR #^XF,#PR730$_MCESR ;CLEAR NON-EX MEMORY CONDITION  
011F 1165  
011F 1169  
011F 1170  
50 08 D0 011F 1172 MOVL #<1@NEX>,R0 ;SETUP  
0C 6E D1 0122 1173 CMPL (SP),#^X0C ;IS THIS A 730 FRAME?  
04 13 0125 1174 BEQL 50$ ;YES, THEN DON'T CHECK FURTHER  
50 24 AE D0 0127 1175 MOVL MCK_BER(SP),R0 ;SAVE BUS ERROR REGISTER  
5E 52 D0 012B 1176 50$: MOVL R2,SP ;CLEAR MCKECK INFO FROM STACK  
E2 50 03 E1 012E 1177 BBC #NEX,R0,OK ;MEMORY EXISTS, PARITY FAILURE  
0132 1179  
0132 1186  
0132 1188 NONEX_DEV: ;  
50 D4 0132 1189 CLRL R0 ;SET STATUS TO FAILURE  
0134 1190 TEST_DONE: ;  
04 A1 8ED0 0134 1191 POPL 4(R1) ;RESTORE SYSTEM MCKECK HANDLER  
0138 1192 TEST_DONE_2: ;  
06 BA 0138 1193 POPR #^M<R1,R2> ;RESTORE REGISTERS  
05 013A 1194 RSB ;RETURN RESULT TO CALLER  
013B 1195 .DISABLE LSB
```



```
013B 1197 .SBTTL ADPLINK - LINK ADAPTER CONTROL BLOCK INTO ADP LIST
013B 1198 :+
013B 1199 : ADPLINK LINKS THE ADAPTER CONTROL BLOCK TO THE END OF THE ADP LIST
013B 1200 :
013B 1201 : INPUT:
013B 1202 : R2 - ADDRESS OF NEW ADP
013B 1203 : OUTPUTS:
013B 1204 : ADP IS LINK TO THE END OF THE ADPLIST LOCATED BY IOC$GL_ADPLIST.
013B 1205 : R0,R1 destroyed.
013B 1206 :-
013B 1207
013B 1208 ADPLINK::
50 FFFFFFFC'9F 9E 013B 1209 MOVAB @#<IOC$GL_ADPLIST-ADP$L_LINK>,R0
0142 1210 : START OF LIST
51 04 A0 D0 0142 1211 10$: MOVL ADP$L_LINK(R0),R1 : FLINK TO FIRST ENTRY
05 13 0146 1212 BEQL 20$ : AT END
50 51 D0 0148 1213 MOVL R1,R0 : TRY AGAIN
04 A0 52 D0 014B 1214 BRB 10$ :
05 014D 1215 20$: MOVL R2,ADP$L_LINK(R0) : CHAIN NEW ADP TO END OF LIST
0151 1216 RSB : AND RETURN
0152 1217
0152 1218 .END
```

ERRSUB730
Symbol table

- ERROR SUBROUTINES FOR VAX 11/730 ^{H 7}

16-SEP-1984 00:54:20 VAX/VMS Macro V04-00
13-SEP-1984 15:49:22 [SYSLOA.SRC]ERRSUB.MAR;5

Page 19
(15)

```
ADPSL_CSR      = 00000000
ADPSL_LINK     = 00000004
ADPSW-ADPTYPE  = 0000000E
ADPLINK        = 0000013B RG 03
ADP-TBL-DWN    = 00000062 R 03
ADP-TBL-UP     = 0000007A R 03
BQOSL-UMR-DIS  = 00000024
BQOSW-VERSION  = 00000010
BTDSK-CONSOLE  = 00000040
C750-LIKE      = 00000001
C780-LIKE      = 00000000
CIS$SHUTDOWN   = ***** X 03
CPU TYPE       = 00000003
EMBSL-CR-CODE  = 000000F4
EMBSL-CR-CPUREG = 00000094
EXESDUMPCPUREG = 00000092 RG 03
EXE$EXTRA1     = 00000000 RG 01
EXE$EXTRA10    = 00000000 RG 01
EXE$EXTRA2     = 00000000 RG 01
EXE$EXTRA3     = 00000000 RG 01
EXE$EXTRA4     = 00000000 RG 01
EXE$EXTRA5     = 00000000 RG 01
EXE$EXTRA6     = 00000000 RG 01
EXE$EXTRA7     = 00000000 RG 01
EXE$EXTRA8     = 00000000 RG 01
EXE$EXTRA9     = 00000000 RG 01
EXE$GL_FLAGS   = ***** X 03
EXE$GL-SCB     = ***** X 03
EXE$INIBOOTADP = 00000000 RG 03
EXE$INIPROCREG = 000000BA RG 03
EXE$READP TODR = 000000A4 RG 03
EXE$READ TODR  = 000000A4 RG 03
EXE$REGRESTOR  = 000000B3 RG 03
EXE$REGSAVE    = 000000AC RG 03
EXE$SHUTDOWNADP = 0000003B RG 03
EXE$STARTUPADP = 00000033 RG 03
EXE$TEST_CSR   = 000000EC RG 03
EXE$V-CR$ENABL = ***** X 03
EXE$V-NOLOCK   = ***** X 03
EXE$WRITEP TODR = 000000A8 RG 03
EXE$WRITE TODR = 000000A8 RG 03
INI UBADP      = 0000000B R 03
IOC$GL ADPLIST = ***** X 03
MASINITIAL     = ***** X 03
MBASINITIAL    = ***** X 03
MCHK HANDLER   = 0000011C R 03
MCK BER        = 00000024
MMG$GL-SBICONF = ***** X 03
NEX            = 00000003
NONEX_DEV      = 00000132 R 03
OK             = 00000114 R 03
PR$-ICCS       = 00000018
PR$-SID-TYP730 = 00000003
PR$-SID-TYP750 = 00000002
PR$-SID-TYP780 = 00000001
PR$-SID-TYP790 = 00000004
PR$-SID-TYPUV1 = 00000007
```

```
PR730$-ACCS    = 00000028
PR730$-ICR     = 0000001A
PR730$-MCESR   = 00000026
PR730$-NICR    = 00000019
PR730$-PME     = 0000003D
PR730$-TODR    = 0000001B
PR730$-UBRESET = 00000037
RPB$B-DEVTYPE  = 00000066
RPB$B-ADPVIR   = 00000060
RPB$B-IOVEC    = 00000034
SS$ NORMAL     = 00000001
SYS$CLRSBIA    = 000000EB RG 03
TEST_DONE      = 00000134 R 03
TEST_DONE_2    = 00000138 R 03
UBAS$INITIAL   = ***** X 03
UBAS$MAP       = 00000800
```

ER
VO

+-----+
! Psect synopsis !
+-----+

PSECT name	Allocation	PSECT No.	Attributes
. ABS :	00000000 (0.)	00 (0.)	NOPIC USR CON ABS LCL NOSHR NOEXE NORD NOWRT NOVEC BYTE
. BLANK :	00000001 (1.)	01 (1.)	NOPIC USR CON REL LCL NOSHR EXE RD WRT NOVEC BYTE
\$ABSS	00000000 (0.)	02 (2.)	NOPIC USR CON ABS LCL NOSHR EXE RD WRT NOVEC BYTE
SYSLOA	00000152 (338.)	03 (3.)	NOPIC USR CON REL LCL NOSHR EXE RD WRT NOVEC LONG

+-----+
! Performance indicators !
+-----+

Phase	Page faults	CPU Time	Elapsed Time
Initialization	29	00:00:00.05	00:00:01.01
Command processing	107	00:00:00.48	00:00:05.05
Pass 1	343	00:00:07.38	00:00:29.02
Symbol table sort	0	00:00:01.06	00:00:04.97
Pass 2	131	00:00:01.98	00:00:10.41
Symbol table output	9	00:00:00.05	00:00:00.05
Psect synopsis output	2	00:00:00.02	00:00:00.01
Cross-reference output	0	00:00:00.00	00:00:00.00
Assembler run totals	623	00:00:11.02	00:00:50.53

The working set limit was 1500 pages.

70472 bytes (138 pages) of virtual memory were used to buffer the intermediate code.

There were 60 pages of symbol table space allocated to hold 1061 non-local and 14 local symbols.

1222 source lines were read in Pass 1, producing 16 object records in Pass 2.

20 pages of virtual memory were used to define 19 macros.

+-----+
! Macro library statistics !
+-----+

Macro library name	Macros defined
-\$255\$DUA28:[SYS.OBJ]LIB.MLB;1	10
-\$255\$DUA28:[SYSLIB]STARLET.MLB;2	6
TOTALS (all libraries)	16

1124 GETS were required to define 16 macros.

There were no errors, warnings or information messages.

MACRO/LIS=LIS\$:ERRSUB730/OBJ=OBJ\$:ERRSUB730 MSRC\$:CPUSW730/UPDATE=(ENH\$:CPUSW730)+MSRC\$:ERRSUB/UPDATE=(ENH\$:ERRSUB)+EXECML\$/LIB

0395

AH - BT13A - SE

DIGITAL EQUIPMENT CORPORATION

ERRSUB790
LISERRSUBUV1
LIS

ERRSUB750
LIS